



08 - 01 - 02

DT Rec'd PCT/PTO 31 JUL 2002
Express Mail No.: EV 034303155US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re U.S. Patent Application No: 10/009,980 ✓
890

Title: **ARRANGEMENT FOR OPTICAL EVALUATION OF AN OBJECT ARRAY**

Inventor(s): **Stefan Schmidt**

Filing Date: **October 26, 2001**

Atty. Docket No: **21195.PUS**

BOX MISSING PARTS
Commissioner for Patents
Washington D.C. 20231

RECEIVED
FEB 14 2003
TC 2000 MAIL ROOM

7/ Sub Spec
4-11-03
Hayes

STATEMENT UNDER M.P.E.P. 608.01(q)
Substitute Specification

I, **Eugene E. Renz, Jr.**, Reg. no. **19,557**, the Attorney of record for the applicants, hereby submit a substitute specification totaling 7 sheets (comprising pages **1 to 7** of description) to replace pages **1 to 7** of the description of application number **10/009,980** filed **October 26, 2001**. Applicant avers that this **seven (7)** page substitute specification contains no new matter.

Marked-up Version of Pages **1 to 7** original specification to be replaced by:

Substitute specification submitted consisting of Pages **1 to 6** submitted herewith.

The substitute specification enclosed herewith is not intended to replace the **four (4)** sheets of drawings.

The substitute specification enclosed is not intended to replace the **two (2)** pages of claims as filed.


I hereby declare that all statements made herein of my own knowledge are true; that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Respectfully submitted,

EUGENE E. RENZ, JR.
Attorney of Record
Registration No. 19,557

Telephone:
(610) 565-6090
Facsimile:
(610) 566-9790
P. O. Box 2056
205 North Monroe Street
Media, PA 19063-9056
renzassoc@earthlink.net
F:\idx90-21195\transmittalsubspec.001

Date: July 31, 2002



PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of : Docket NO.: 21195.PUS

Stefan Schmidt :

:Statement Under MPEP 608.01(q), Marked up version of Substitute
:Specification (7pp.), Clean copy of Substitute Specification (6pp.)
:Information Disclosure Statement, PTO- 1449 and Eight (8)
:References

Serial No.: 10/009,980

890

Filed: October 26, 2001 :

Title: ARRANGEMENT FOR OPTICAL EVALUATION OF AN OBJECT ARRAY

To the Commissioner of Patents and Trademarks:

Sir:

EXPRESS MAIL FILING CERTIFICATE

EXPRESS MAIL MAILING LABEL NO. EV 034303155US

DATE OF DEPOSIT: 7/31/2002

RECEIVED
FEB 14 2003
TC 2800 MAIL ROOM

I hereby certify that the above-identified correspondence is being deposited with the United States Postal Service EXPRESS MAIL POST OFFICE TO ADDRESSEE Service under 37 C.F.R. § 1.10 on the date indicated above in an envelope addressed to: Commissioner of Patents and Trademarks, BOX MISSING PARTS, Washington, D.C. 20231.

Respectfully submitted,

Donna Marie Racine
Certified Paralegal

Telephone:

(610) 565-6090

Facsimile:

(610) 566-9790

P.O. Box 2056

205 North Monroe Street

Media, PA 19063-9056

renzassoc@earthlink.net

F:\idx90\21195\expressmail.001



ARRANGEMENT FOR OPTICAL EVALUATION OF AN OBJECT ARRAY

CROSS REFERENCE TO RELATED APPLICATION

This application claims priority of German patent application no. 199 19092.5, filed April 27, 1999, the complete disclosure of which is hereby incorporated by reference.

5 FIELD OF INVENTION

The invention relates to an arrangement for optical evaluation for an of an object array.

SUMMARY OF THE INVENTION

10 The invention provides for an arrangement for optical evaluation of an object array, comprising a detector array, a microlens array, which is disposed in front of the object array, as viewed in the direction of the detector array, a field lens, which is disposed in front of the object array, as viewed in the direction of the detector array, a light source, the radiation of which is coupled in by means of a beam splitter between the field lens and an objective, wherein the objective, together with the field lens, simultaneously
15 images all pupils of the microlens array onto the detector array.

The invention will be explained in more detail below, by way of example and with reference to the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The objects of the present invention and various features and details of the operation and construction thereof are hereinafter more fully set forth with reference to the accompanying drawings, in which:

Fig. 1 shows the entire beam path, for example in fluorescence measurement;

Fig. 2 shows the beam path in absorption measurement;

Fig. 3 shows the beam path in luminescence measurement;

25 Fig. 4 shows the beam path without the MLA.

Description of the beam path

The optical assembly is divided into three essential components.

1. A microlens array (MLA) (2) for focusing light into small areas (sample volumes) of the wells (1a-1d) of a microtiter plate (MTP) (1), which are filled with a sample substance. In the case of fluorescence or luminescence applications, the MLA (2) also serves to collect light emitted from the sample volume.

2. A telescope arrangement of lenses 3, 11 and of a collimator (14) for illuminating the microlens array 2. As the light source, the output of an optical fiber may be used, or, as represented in the Figures, the lamp itself.

3. A field lens (3) and an objective (6) for telecentric imaging of the pupils of the MLA (2) on a CCD-array detector (7).

The microlens array consists of a regular arrangement of small lenses or objectives. Preferably, the the microlenses are arranged to form a rectangular grid. In any case, the arrangement of the microlenses is adapted to the geometry of the sample container array or of the MTP, respectively.

The front lens (3) of the telescope for illumination, which lens faces the MLA (2), also serves as field lens for the telecentric imaging of the MLA pupils.

1. The excitation beam path

The light exiting from the optical fiber (15) is collected by a collimator (14). This collimator (14), together with the small telescope lens (11), which has a short focal length, images the optical fiber output into the intermediate image plane (9) of the telescope 3, 11. The large telescope lens (3), which has a long focal length, picks up the light from the intermediate image plane (9) and transforms it into a bundle of small divergence, by which the MLA (2) is illuminated on its side facing away from the sample. Each individual lens (2a..2d) of the MLA (2) then focuses the light into a respective well (1a..1d) of the microtiter plate (1).

The aperture diaphragm (12) of the illuminating telescope and attenuating filter (13) are disposed between the collimator (14) and the small telescope lens (11). The aperture diaphragm (12) defines the shape of the beam cross-section and keeps superfluous light away from the beam path. This serves to reduce signal cross-talk and

scattered light background in the detection beam path. The aperture diaphragm (12) is disposed in a plane which is conjugated to the plane of the microlens pupils. Thus, the aperture lens (12) forms a small-scale copy of the external outline of the MLA (2). The aperture diaphragm (12) may also be embodied as a disk diaphragm array for improved reduction of scattered light.

The field diaphragm (9a) of the illuminating telescope is disposed in the intermediate image plane (9). The intermediate image plane (9) is imaged into the wells (1a..1d) of the MTP (1) by the large telescope lens (3) and the lenses (2a..2d) of the MLA (2). Thus, the field diaphragm (9a) defines the bundle cross-section of the light within the wells (1a..1d).

The excitation filter (10) serves to define the spectral range of the illumination.

The light from the samples is reflected into the beam path, which is also used for detection, via the mirror (8).

Arranging said mirror 8 in front of the objective 6 facilitates the selection of a different mode of illumination.

If the device is used for fluorescence analysis, the mirror (8) is designed as a dichroic beam splitter. The spectral range of the exciting light is reflected, while the spectral range to be detected is transmitted. If the device serves to detect luminescence, reflexion by the mirror 8 can be omitted as well as the illumination, and the beam path will then only comprise the detection beam path, as set forth below.

2. Detection beam path

The light emitted from the sample volume is collimated by the microlenses (2a..2d). One microlens (2a..2d) is assigned to each well (1a..1d) of the MTP (1). The collimated light exiting from the pupils of the microlenses is focused on the intermediate image plane (4), which is conjugated to the intermediate image plane (9) on the excitation side, by the large telescope lens (3), which also serves as field lens for pupil imaging. Thus, the images of the sample volumes from all wells (1a..1d) of the MTP (1) are superimposed in the intermediate image plane (4). The diaphragm (4a) defines the observed sample volume in each well. Preferably, the diaphragm (4a) is the same size as the field diaphragm (9a) of the illumination.

The diaphragm (4a) also constitutes the aperture diaphragm for pupil imaging. The imaging of the pupils of the microlenses (2a..2d) onto the CCD-array detector (7) is carried out by the objective (6).

The emission filter (5) serves to define the detected spectral range.

5 The reflecting mirrors (16,17,18) serve to bring the beam path into a compact shape. To this end, multiple folding by a multiplicity of mirrors is conceivable.

Description of modes of measurement

10 In principle, different methods of measurement are applicable to the samples contained in the MTP. Based on the above-described beam path, the measurements according to a method may be carried out in several wells at the same time. So far, the following methods of measurement have been taken into consideration:

1. Absorption
2. Fluorescence
3. Luminescence
- 15 4. Time-dependent fluorescence detection
5. Polarization-dependent fluorescence or absorption

Absorption

In absorption measurement, only the excitation beam path is used.

20 The beam splitter 8 may be replaced by a full mirror. The detection of the light transmitted through the sample is effected by means of a photodiode array (19), which is located as closely behind the sample containers as possible.

The above-described beam path allows the side of the MLA facing away from the samples to be homogeneously illuminated so that each well is traversed by light of the same intensity. For absorption purposes, the MLA is to be adapted such that the walls
25 of the wells do not limit the beams formed by the microlenses and that each light bundle impinges fully on its associated detector surface (19a..19d) of the photodiode array.

This means that, for certain MTPs or sample containers, exchangeable MLAs and field diaphragms 9a may be provided, which are optimized with regard to their focal lengths and radiuses of curvature.

Fluorescence

In fluorescence measurement, excitation is effected in the same manner as in the case of absorption measurement. However, the mirror (8) is replaced by a dichroic beam splitter having high transmission for the light emitted by the sample.

5 The design of the MLA depends on the excitation, which should be as selective as possible, and on the detection of a small volume within the well, i.e. a sufficient chromatic correction requires a high numeric aperture (equal to, or greater than, 0.5).

Luminescence

Since the sample emits light by itself, only the detection beam path is used.

10 The beam splitter 8 may be swivelled out.

It is possible, in general and also in absorption measurements, to omit the MLA and to image an image of the MTP bottom directly onto the CCD-array detector. In this case, the entire plate can be read at once, regardless of the number of wells it contains. Although this means slight losses in sensitivity, all channels may be read simultaneously even where there are a large number of channels.

15

Fluorescence detection over time

In time-dependent fluorescence detection, the same beam path is used as in fluorescence detection.

20 Excitation is effected by a light source capable of generating short light pulses (ca. 1 ns), i.e., for example, a suitable flash lamp.

The detector used should be capable of carrying out, after a delay of about the length of the excitation impulse, a measurement having an integration time of about the same length, synchronized to the illumination clock.

A microchannel-amplified camera is suitable for this purpose.

25 The intensity of fluorescence remaining after said delay is measured.

Polarization-dependent fluorescence

This requires a polarization-maintaining optical system. The fluorescence intensity in the polarization direction orthogonal to the excitation light is measured.

To this end, polarizing filters, which preferably polarize perpendicular to each other, may be provided in front of filters 5 and 10.

Although a certain preferred embodiment has been shown and described, it should be understood that many changes and modifications may be made therein without departing from the spirit and scope of the appended claims.

ARRANGEMENT FOR OPTICAL EVALUATION OF AN OBJECT ARRAY

CROSS REFERENCE TO RELATED APPLICATION

This application claims priority of German patent application no. 199 19092.5, filed April 27, 1999, the complete disclosure of which is hereby incorporated by reference.

FIELD OF THE INVENTION

~~The present invention relates to improvements in~~ an arrangement for optical evaluation for an of an object array.

SUMMARY OF THE INVENTION

The invention provides for an arrangement for optical evaluation of an object array: —, comprising a detector array, a microlens array, which is disposed in front of the object array, as viewed in the direction of the detector array, a field lens, which is disposed in front of the object array, as viewed in the direction of the detector array, a light source, the radiation of which is coupled in by means of a beam splitter between the field lens and an objective, wherein the objective, together with the field lens, simultaneously images all pupils of the microlens array onto the detector array.

The invention will be explained in more detail below, by way of example and with reference to the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

~~These and other~~ The objects of the present invention and various features and details of the operation and construction thereof are hereinafter more fully set forth with reference to the accompanying drawings, wherein:

The invention is explained in greater detail on the basis of an exemplary embodiment, which is illustrated in the drawing:-

in which:



Fig. 1 shows the entire beam path, for example; in fluorescence measurement;

Fig. 2 shows the beam path in absorption measurement;

Fig. 3 shows the beam path in luminescence measurement; and

Fig. 4 shows the beam path without the MLA.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Description of the beam path

10

The optical assembly- is divided into three essential components.

15

1. A microlens array (MLA) (2) for focusing light into small areas (sample volumes) of the wells (1a-1d) of a microtiter plate (MTP) (1), which are filled with a sample substance. In the case of fluorescence or luminescence applications, the MLA (2) also serves to collect light emitted from the sample volume.

2. A telescope arrangement of lenses 3, 11 and of a collimator (14) for illuminating the microlens array 2. As the light source, the output of an optical fiber may be used, or, as represented in the Figures, the lamp itself.

20

3. A field lens (3) and an objective-lens (6) for telecentric imaging of the pupils of the MLA (2) on a CCD-array detector (7).

The microlens array consists of a regular arrangement of small lenses or objectives. Preferably, the the microlenses are arranged to form a rectangular grid. In any case, the arrangement of the microlenses is adapted to the geometry of the sample container array or of the MTP, respectively.

The front lens (3) of the telescope for illumination, which lens faces the MLA (2), also serves as field lens for the telecentric imaging of the MLA pupils.

1. The excitation beam path

The light exiting from the optical fiber (15) is collected by a collimator (14). This collimator (14), together with the small telescope lens (11), which has a short focal length, images the optical fiber output into the intermediate image plane (9) of the telescope 3, 11. The large telescope lens (3), which has a long focal length, picks up the light from the intermediate image plane (9) and transforms it into a bundle of small divergence, by which the MLA (2) is illuminated on its side facing away from the sample. Each individual lens (2a..2d) of the MLA (2) then focuses the light into a respective well (1a..1d) of the microtiter plate (1).

The aperture diaphragm (12) of the illuminating telescope and attenuating filter (13) are disposed between the collimator (14) and the small telescope lens (11). The aperture diaphragm (12) defines the shape of the beam cross-section and keeps superfluous light away from the beam path. This serves to reduce signal cross-talk and scattered light background in the detection beam path. The aperture diaphragm (12) is disposed in a plane which is conjugated to the plane of the microlens pupils. Thus, the aperture lens (12) forms a small-scale copy of the external outline of the MLA (2). The aperture diaphragm (12) may also be embodied as a disk diaphragm array for improved reduction of scattered light.

The field diaphragm (9a) of the illuminating telescope is disposed in the intermediate image plane (9). The intermediate image plane (9) is imaged into the wells (1a..1d) of the MTP (1) by the large telescope lens (3) and the lenses (2a..2d) of the MLA (2). Thus, the field diaphragm (9a) defines the bundle cross-section of the light within the wells (1a..1d).

The excitation filter (10) serves to define the spectral range of the illumination.

The light from the samples is reflected into the beam path, which is also used for detection, via the mirror (8).

Arranging said mirror 8 in front of the objective 6 facilitates the selection of a different mode of illumination.

If the device is used for fluorescence analysis, the mirror (8) is designed as a dichroic beam splitter. The spectral range of the exciting light is reflected, while the spectral range to be detected is transmitted. If the device serves to detect luminescence, reflexingreflexion by the mirror 8 can be omitted as well as the illumination, and the beam path will then only comprise the detection beam path, as set forth below.

2. Detection beam path

The light emitted from the sample volume is collimated by the microlenses (2a..2d). One microlens (2a..2d) is assigned to each well (1a..1d) of the MTP (1). The collimated light exiting from the pupils of the microlenses is focused on the intermediate image plane (4), which is conjugated to the intermediate image plane (9) on the excitation side, by the large telescope lens (3), which also serves as field lens for pupil imaging. Thus, the images of the sample volumes from all wells (1a..1d) of the MTP (1) are superimposed in the intermediate image plane (4). The diaphragm (4a) defines the observed sample volume in each well. Preferably, the diaphragm (4a) is the same size as the field diaphragm (9a) of the illumination.

The diaphragm (4a) also constitutes the aperture diaphragm for pupil imaging. The imaging of the pupils of the microlenses (2a..2d) onto the CCD-array detector (7) is carried out by the objective lens(6).

The emission filter (5) serves to define the detected spectral range.

The reflecting mirrors (16,17,18) serve to bring the beam path into a compact shape. To this end, multiple folding by a multiplicity of mirrors is conceivable.

Description of modes of measurement

In principle, different methods of measurement are applicable to the samples contained in the MTP. Based on the above-described beam path, the measurements according to a method may be carried out in several wells at the same time. So far, the following methods of measurement have been taken into consideration:

1 Absorption

2. Fluorescence

3. Luminescence

4. Time-dependent fluorescence detection

5. Polarization-dependent fluorescence (or absorption)

Absorption

In absorption measurement, only the excitation beam path is used.

The beam splitter 8 may be replaced by a full mirror. The detection of the light transmitted through the sample is effected by means of a photodiode array (19), which is located as closely behind the sample containers as possible.

The above-described beam path allows the side of the MLA facing away from the samples to be homogeneously illuminated so that each well is traversed by light of the same intensity. For absorption purposes, the MLA is to be adapted such that the walls of the wells do not limit the beams formed by the microlenses and that each light bundle impinges fully on its associated detector surface (19a..19d) of the photodiode array.

This means that, for certain MTPs or sample containers, exchangeable MLAs and field diaphragms 9a may be provided, which are optimized with regard to their focal lengths and radiuses of curvature.

Fluorescence

5 In fluorescence measurement, excitation is effected in the same manner as in the case of absorption measurement. However, the mirror (8) is replaced by a dichroic beam splitter having high transmission for the light emitted by the sample.

10 The design of the MLA depends on the excitation, which should be as selective as possible, and on the detection of a small volume within the well, i.e. a sufficient chromatic correction requires a high numeric aperture (equal to, or greater than, 0.5).

Luminescence

Since the sample emits light by itself, only the detection beam path is used.-
The beam splitter 8 may be swivelled out.

15 It is possible, in general and also in absorption measurements, to omit the MLA and to image an image of the MTP bottom directly onto the CCD-array detector. In this case, the entire plate can be read at once, regardless of the number of wells it contains. Although this means slight losses in sensitivity, all channels may be read simultaneously even where there are a large number of channels.

Fluorescence detection over time

In time-dependent fluorescence detection, the same beam path is used as in fluorescence detection.

Excitation is effected by a light source capable of generating short light pulses (ca. 1 ns), i.e., for example, a suitable flash lamp.

The detector used should be capable of carrying out, after a delay of about the length of the excitation impulse, a measurement having an integration time of about the same length, synchronized to the illumination clock.

A microchannel-amplified camera is suitable for this purpose.

The intensity of fluorescence remaining after said delay is measured.

Polarization-dependent fluorescence

This requires a polarization-maintaining optical system. The fluorescence intensity in the polarization direction orthogonal to the excitation light is measured.

To this end, polarizing filters, which preferably polarize perpendicular to each other, may be provided in front of filters 5 and 10.

Even though

Although a particular embodiment of the invention has been illustrated and described herein, it is not intended to limit the invention and certain preferred embodiment has been shown and described, it should be understood that many changes and modifications may be made therein within the scope without departing from the spirit and scope of the appended claims.